CE 0085

DVGW CERT

EU type examination certificate

EU-Baumusterprüfbescheinigung

CE-0085CT0184
Product Identification No.
Produkt-Identnummer

Field of Application ***Anwendungsbereich***	EU Gas Appliances Regulation (EU/2016/426) *EU-Gasgeräteverordnung (EU/2016/426)*
Distributor ***Vertreiber***	Ferroli S.p.A. Via Ritonda 78A, I-37047 San Bonifacio (VR)
Product Category ***Produktart***	Boilers with flue systems: Condensing combi water heater (3204)
Product Description ***Produktbezeichnung***	Condensing combi water heater optional also as condensing water heater
Model ***Modell***	LAMBORGHINI CALORECLIMA iXinox/IDOLA UI HYBRID/RAGGIO...
Countries of Destination ***Bestimmungsländer***	AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GR, HR, HU, IE, IT, LT, LU, LV, MT, NL, NO, PL, PT, RO, SE, SI, SK
Test Reports ***Prüfberichte***	supplement test: K 2107 2021 B40 from 15.06.2021 (TRG) supplement test: K 2107 2021 E39 from 15.06.2021 (TRG)
Test Basis ***Prüfgrundlagen***	EU/2016/426 A III B (09.03.2016) DIN EN 15502-1 (01.10.2015) DIN EN 15502-2-1 (01.09.2017)
Date of Expiry / File No. ***Ablaufdatum / AZ***	06.07.2028 / 21-0575-GEA

70028-04-A-DE

06.12.2021 Pz B-1/2
Date, Issued by, Sheet, Head of Certification Body
Datum, Bearbeiter, Blatt, Leiter der Zertifizierungsstelle

DAkkS
Deutsche Akkreditierungsstelle
D-ZE-16028-01-01

DVGW CERT GmbH
Zertifizierungsstelle
Josef-Wirmer-Str. 1-3
53123 Bonn
Tel. +49 228 91 88 - 888
Fax +49 228 91 88 - 993
www.dvgw-cert.com
info@dvgw-cert.com

Type *Typ*	Technical Data *Technische Daten*	Remarks *Bemerkungen*
LAMBORGHINI CALORECLIMA iXinox SMART 24 C; LAMBORGHINI CALORECLIMA RAGGIO 24 C	nominal heat output: 2,8...20,0 kW heat input (Hi): 2,9...20,4 (drinking water: ...25,0) kW	
LAMBORGHINI CALORECLIMA IDOLA UI HYBRID H 08	nominal heat output: 2,8...24,0 kW heat input (Hi): 2,9...24,5 kW	
LAMBORGHINI ... iXinox SMART 28 C; LAMBORGHINI ... IDOLA UI HYBRID C 08; LAMBORGHINI ... RAGGIO 28 C	nominal heat output: 2,8...24,0 kW heat input (Hi): 2,9...24,5 (drinking water: ...28,5) kW	
LAMBORGHINI CALORECLIMA iXinox SMART 34 C; LAMBORGHINI CALORECLIMA RAGGIO 34 C	nominal heat output: 2,8...30,0 kW heat input (Hi): 2,9...30,6 (drinking water: ...34,7) kW	
LAMBORGHINI CALORECLIMA iXinox 18 H	nominal heat output: 4,9...18,0 kW heat input (Hi): 5,0...18,4 kW	
LAMBORGHINI CALORECLIMA iXinox 24 C	nominal heat output: 4,9...20,0 kW heat input (Hi): 5,0...20,4 (drinking water: ...25,0) kW	
LAMBORGHINI CALORECLIMA iXinox 28 C; LAMBORGHINI CALORECLIMA iXinox 24 H; LAMBORGHINI CALORECLIMA iXinox 28 K 50	nominal heat output: 4,9...24,0 kW heat input (Hi): 5,0...24,5 (drinking water: ...28,5) kW	
LAMBORGHINI CALORECLIMA iXinox 34 C; LAMBORGHINI CALORECLIMA iXinox 30 H; LAMBORGHINI CALORECLIMA iXinox 34 K 50	nominal heat output: 6,3...30,0 kW heat input (Hi): 6,4...30,6 (drinking water: ...34,7) kW	
LAMBORGHINI CALORECLIMA iXinox 45 H; LAMBORGHINI CALORECLIMA iXinox 45 C	nominal heat output: 6,3...42,8 kW heat input (Hi): 6,4...43,8 (drinking water: ...43,8) kW	

Hints of Utilization /Remarks
Verwendungshinweise / Bemerkungen

Flue types B23, B33, C13(x), C(10), C(11), C23, C33(x), C43(x), C53(x), C63(x), C83(x), C93(x): according to installation manual with flue system of Groppalli (2592-CPR-001)
Approved appliance categories, supply pressures and countries of destination:
I2N (20/25 mbar): BE, FR; I2N (20 mbar): CZ, ES, GR, PT, SI; I2E (20 mbar): LU, RO; I2H (20 mbar): FR, NL
I3B (37 mbar): ES, IE; I3B/P (30 mbar): BE; I3B/P (37 mbar): GR, PT
II2E3B/P (20, 13, 30 mbar): PL; II2E3B/P (20, 50 mbar): AL, DE, MK, PL
II2H3B/P (20, 30 mbar): BG, CY, DK, EE, FI, HR, HU, IS, IT, LT, MT, NO, RO, SE, SI, SK, TR
II2H3B/P (20, 37 mbar): GR, HR, LV; II2H3B/P (20, 50 mbar): AT, CH, CY, CZ, LU
II2H3P (20, 37 mbar): ES, GB, IE, PT
II2H3+ (20, 30/37mbar): CH, CY, CZ, ES, GB, GR, IE, IT, PT, SI, SK, TR
II2ELL3B/P (20, 50 mbar): DE; II2E+3+ (20/25, 30/37 mbar): BE, FR
II2E+3P (20/25, 37 mbar): BE; II2E+3B/P (20/25, 37 mbar): FR; II2HS3B/P (25, 30 und 50 mbar): HU
II2HM3B/P (20, 30 mbar): IT; II2HM3+ (20, 30/37 mbar): IT
II2L3B/P (25, 30 mbar) and II2EK3B/P (20/25, 30 mbar): NL
II2ELw3B/P (20, 20, 30 mbar): PL
II2ELwLs3B/P (20, 20, 13, 30 mbar): PL
In the NON-EU countries the CE-marking will be accepted as conformity approval if the Gas Appliance Regulation EU/2016/426 is transferred into national law by this countries.

DVGW